CubicSecure

Smart automatic water shut off valve, flow meter and leak detector. CubicSecure measures your water flow in real time and detects water leaks immediately. It protects your home from damage caused by micro-leaks and broken water pipes. The compact design makes CubicSecure easy to install and even fits in water cabinets.



DATASHEET



HARDWARE SPECIFICATIONS

Pipe connection

G20 Eurocone external thread (DN20)

Weight

720 grams

Dimensions

Height: 85, width: 71, length: 110 mm

Power supply

5VDC 2A Power supply, micro-USB cable

(EU-plug), 1m cable

Power usage (average)

~6 kWh/year (with Wi-Fi connected)

Valve open/close time

~10 seconds

CONNECTIVITY

WiFi

2.4 GHz, (802.11 b/g/n) Report interval: 1 hour

ENVIRONMENT

Environment

5 °C - 30 °C, indoor usage (not waterproof)

Area of use

Villa, terraced house, apartment

MEASUREMENT SPECIFICATIONS

Maximum flow rate

4000 l/h

Flow rate accuracy

Max ±3% error

Water temperature

0.1°C - 70°C

Water temperature accuracy

Max ±2% error

Pressure

PN10

Maximum water pressure (15min)

16 Bar

Water pressure accuracy

Max ±10% error

Micro-leak detection

>0.3 bar pressure loss (approx. 0,01 l/h)

Medium leak detection

>6 I/h for at least 45 minutes

Large leak detection

>1500 l/h for at least 90 seconds

